



| | |
|-----------------------------|-------------|
| MODEL : | MM3500-M |
| ENGINE MODEL : | MM210F |
| DISPLACEMENT(ml): | 208 |
| Continuous Working Time(h): | 11 |
| Rated Frequency(Hz): | 50/60 |
| Max Power(kw/rpm): | 3 |
| Rated Power(kw/rpm): | 2.5 |
| Voltage(V): | 230/120-240 |
| Fuel Tank Capacity(L): | 15 |
| Oil Capacity(L): | 0.6 |
| N.W/G.W(kg): | 48/50 |
| Dimension(mm): | 610*455*500 |



| | |
|-----------------------------|-------------|
| MODEL : | MM6500-G |
| ENGINE MODEL : | MM390F |
| DISPLACEMENT(ml): | 389 |
| Continuous Working Time(h): | 15 |
| Rated Frequency(Hz): | 50/60 |
| Max Power(kw/rpm): | 5.5 |
| Rated Power(kw/rpm): | 5 |
| Voltage(V): | 230/120-240 |
| Fuel Tank Capacity(L): | 25 |
| Oil Capacity(L): | 11 |
| N.W/G.W(kg): | 78/80 |
| Dimension(mm): | 700*560*575 |

石頭金

Sichuan MetalMiracle Industry Corp.



| | |
|-----------------------------|-------------|
| MODEL : | MM7500X-G |
| ENGINE MODEL : | MM420F |
| DISPLACEMENT(ml): | 420 |
| Continuous Working Time(h): | 10 |
| Rated Frequency(Hz): | 50/60 |
| Max Power(kw/rpm): | 7 |
| Rated Power(kw/rpm): | 6.5 |
| Voltage(V): | 230/120-240 |
| Fuel Tank Capacity(L): | 25 |
| Oil Capacity(L): | 11 |
| N.W/G.W(kg): | 88/90 |
| Dimension(mm): | 720*560*575 |



| | |
|-----------------------------|-------------|
| MODEL : | MM6500X-M |
| ENGINE MODEL : | MM390F |
| DISPLACEMENT(ml): | 389 |
| Continuous Working Time(h): | 15 |
| Rated Frequency(Hz): | 50/60 |
| Max Power(kw/rpm): | 5.5 |
| Rated Power(kw/rpm): | 5 |
| Voltage(V): | 230/120-240 |
| Fuel Tank Capacity(L): | 25 |
| Oil Capacity(L): | 11 |
| N.W/G.W(kg): | 78/80 |
| Dimension(mm): | 720*560*575 |



| | |
|-----------------------------|-------------|
| Model : | MM6500X-L |
| Engine Model : | MM390F |
| Displacement(ml): | 390 |
| Continuous Working Time(h): | 15 |
| Rated Frequency(Hz): | 50/60 |
| Max Power(kw/rpm): | 5.5 |
| Rated Power(kw/rpm): | 5 |
| Voltage(V): | 230/120-240 |
| Fuel Tank Capacity(L): | 25 |
| Oil Capacity(L): | 11 |
| N.W/G.W(kg): | 78/80 |
| Dimension(mm): | 720*560*575 |



| | |
|-----------------------------|-------------|
| Model : | MM3500X-L |
| Engine Model : | MM210F |
| Displacement(ml): | 208 |
| Continuous Working Time(h): | 11 |
| Rated Frequency(Hz): | 50/60 |
| Max Power(kw/rpm): | 3 |
| Rated Power(kw/rpm): | 2.5 |
| Voltage(V): | 230/120-240 |
| Fuel Tank Capacity(L): | 15 |
| Oil Capacity(L): | 0.6 |
| N.W/G.W(kg): | 45/47 |
| Dimension(mm): | 620*455*465 |



| | |
|-----------------------------|------------------------|
| Model : | MM1000E |
| Engine Model : | B&S/KOHLER/HONDA/CHINA |
| Displacement(cc): | 678 |
| Starting System: | Electric Start |
| Oil Capacity(L): | 3.6 |
| Fuel Tank Capacity(L): | 30 |
| Frequency(Hz): | 50/60 |
| Voltage(V): | 230/230-380/ 120-240 |
| Rated AC output(KVA): | 9/10 |
| Max AC output(KVA): | 10/12 |
| 50%Continuous working time: | 14 |
| Net weight(kg): | 180 |
| Dimension(mm): | 850*630*850 |

NOTE:

The catalog did not include all machinery info. For your special requests for configuration and applications, please do contact us so that meet your demands successfully.

Contact Us

Tianfu Avenue South Section NO.2039,HuaYang,Chengdu Tianfu New Area,China.

Industry area, ChongZhou, Chengdu, China.

Industry area, ChongQing, China.

Mechanical Industry area,Taibai, Maanshan,China.

Tel. 86 28 85718737 Email: agri@metalmiracle.biz